

Specification Table

Download 

CASE	Weight w/ foam	Weight w/o foam	Temp. min. ° F	Temp. max ° F	Bouyancy Lbs. Max	INTERNAL DIMEN. in Inches			EXTERNAL DIMEN. in Inches			Depth in Inches		Colors						Units Master.	PanelFra.	Extras	CASE	
						Length	Width	Height	Length	Width	Height	Lid	Case	Black	Silver	Orange	Yellow	Red	Blue					Clear*
1010	-	0.40	-10°	+200°	0.5	4-7/16	2-15/16	1-11/16	5-7/16	4-1/16	2-7/64			B			Y	R	Bl	C	6		Pick 'N' Pluck™ Foam	1010
1020	-	0.50	-10°	+200°	0.75	5-3/8	3-5/8	1-11/16	6-3/8	4-3/4	2-7/64			B			Y	R	Bl	C	6		Pick 'N' Pluck™ Foam	1020
1030	-	0.54	-10°	+200°	1	6-1/2	2-3/4	2-1/16	7-1/2	3-7/8	2-7/16			B			Y	R	Bl	C	6		Pick 'N' Pluck™ Foam	1030
1040	-	0.68	-10°	+200°	1.25	6-9/16	3-15/16	1-3/4	7-17/32	5-5/64	2-5/32			B			Y	R	Bl	C	6		Pick 'N' Pluck™ Foam	1040
1050	-	0.84	-10°	+200°	1.75	6-9/16	3-15/16	2-3/4	7-17/32	5-5/64	3-1/8			B			Y	R	Bl	C	6		Pick 'N' Pluck™ Foam	1050
1060	-	0.98	-10°	+200°	2.5	8-7/16	4-7/16	2-1/4	9-13/32	5-5/64	2-5/8			B			Y	R	Bl	C	6		Pick 'N' Pluck™ Foam	1060
1120	1.24	1.17	-10°	+210°	7.05	7-3/8	4-7/8	3-1/16	8-1/4	6-9/16	3-9/16	1/2	2-9/16	B	S	O	Y		Bl		6	Y	Panel Frame	1120
1150	1.98	1.76	-10°	+210°	5.95	8-3/8	5-7/8	3-11/16	9-1/4	7-9/16	4-3/8	3/4	2-15/16	B	S	O	Y		Bl		6	Y	Panel Frame	1150
1200	2.87	2.65	-10°	+210°	7.94	9-3/8	7-1/4	4-1/8	10-5/8	9-11/16	4-7/8	1-3/16	2-15/16	B	S	O	Y				6	Y	Panel Frame	1200
1300	3.53	3.09	-10°	+210°	11.9	9-3/8	7-1/4	6-1/8	10-5/8	9-11/16	6-7/8	1-3/16	4-15/16	B	S	O	Y				4	Y	Panel Frame	1300
1400	4.40	3.90	-10°	+210°	20	12	9-1/16	5-3/16	13-3/8	11-5/8	6	1-3/16	4	B	S	O	Y				4	Y	Panel Frame	1400
1420	-	3.78	-10°	+210°	20	13	5	10	15	8-1/2	10-1/2	1	9	B							4		-	1420
1450	6.40	5.60	-10°	+210°	25	14-13/16	10-3/8	6	16	13	6-7/8	1-3/4	4-1/4	B	S	O	Y				4	Y	Panel Frame & Dividers	1450
1470	5.45	3.80	-10°	+210°	20	15-3/4	10-9/16	3-3/4	16-11/16	13-1/16	4-3/8	1-3/8	2-3/8	B							4	Y	Panel Frame	1470
1470NF	-	3.80	-10°	+210°	20	15-3/4	10-9/16	3-3/4	16-11/16	13-1/16	4-3/8	1-3/8	2-3/8	B							4	Y	-	1470NF
1470CC1	6.60	-	-10°	+210°	20	15-3/4	10-9/16	3-3/4	16-11/16	13-1/16	4-3/8	1-3/8	2-3/8	B							4	Y	Lid & Tray	1470CC1
1470AC	6.50	-	-10°	+210°	20	15-3/4	10-9/16	3-3/4	16-11/16	13-1/16	4-3/8	1-3/8	2-3/8	B							4	Y	Lid	1470AC
1470CC2	6.70	-	-10°	+210°	20	15-3/4	10-9/16	3-3/4	16-11/16	13-1/16	4-3/8	1-3/8	2-3/8	B							4	Y	Lid & Foam	1470CC2
1490	6.55	5.20	-10°	+210°	20	17-7/8	11-1/2	4-1/8	19-7/16	13-15/16	4-11/16	1-1/2	2-5/8	B							4	Y	Panel Frame	1490
1490NF	-	5.20	-10°	+210°	20	17-7/8	11-1/2	4-1/8	19-7/16	13-15/16	4-11/16	1-1/2	2-5/8	B							4	Y	Panel Frame	1490NF
1490CC1	7.20	-	-10°	+210°	20	17-7/8	11-1/2	4-1/8	19-7/16	13-15/16	4-11/16	1-1/2	2-5/8	B							4	Y	Lid & Tray	1490CC1
1490AC	7.10	-	-10°	+210°	20	17-7/8	11-1/2	4-1/8	19-7/16	13-15/16	4-11/16	1-1/2	2-5/8	B							4	Y	Lid	1490AC
1490CC2	6.55	-	-10°	+210°	20	17-7/8	11-1/2	4-1/8	19-7/16	13-15/16	4-11/16	1-1/2	2-5/8	B							4	Y	Lid & Foam	1490CC2
1500	7.10	6.50	-10°	+210°	40	17	11-7/16	6-1/8	18-1/2	14-1/16	6-15/16	1-13/16	4-5/16	B	S	O	Y				4	Y	Panel Frame & Div.Lid/Pho/Att.	1500
1520	8.60	8.00	-10°	+210°	40	17-7/8	12-3/4	6-3/4	19-1/8	15-7/16	7-9/16	1-13/16	4-15/16	B	S	O	Y				2	Y	Panel Frame & Dividers	1520
1550	11.90	10.50	-10°	+210°	45	18-15/16	14-7/16	7-3/4	20-11/16	17-3/16	8-9/16	1-13/16	5-15/16	B	S	O	Y				2	Y	Panel Frame & Dividers	1550
1600	14.00	13.00	-10°	+210°	55	21-3/4	16-13/16	7-7/8	24-1/4	19-7/16	8-11/16	1-3/4	6-1/8	B	S	O	Y				2	N	Dividers	1600
1610**	23.25	20.00	-10°	+210°	200	22-3/16	17-1/8	10-9/16	24-9/16	19-5/16	11-15/16	2-1/16	8-1/2	B							1	N	Dividers	1610**
1620**	26.10	24.50	-10°	+210°	200	22-1/16	17	12-9/16	24-13/16	19-3/8	13-7/8	2-1/16	10-1/2	B							1	N	Dividers	1620**

Specification Table of Cases

1650**	30.35	29.40	-10°	+210°	100	29	17-7/8	10-1/2	32-1/2	20-1/2	11-5/16	1-7/8	8-5/8	B	1	N	Div./Lid Organ.	1650**						
1660**	42.00	34.00	-10°	+210°	150	29-1/8	20-11/16	17-5/8	31-1/2	22-7/8	18-7/8	3-1/2	14-1/8	B	1		Div./Lid Organ.	1660**						
1700**	17.00	16.00	-10°	+210°	50	35-3/4	13-13/16	5-1/4	38-1/8	17-13/16	6-1/8	1-3/4	3-1/2	B	1	N	-	1700**						
1750**	25.60	23.50	-10°	+210°	55	50-1/2	13-7/16	5-1/4	53	17-7/16	6-1/16	1-3/4	3-1/2	B	1	N	-	1750**						
CASE	Weight w/ foam	Weight w/o foam	Temp. min. ° F	Temp. max ° F	Bouyancy Lbs. Max	INTERNAL DIMEN. in Inches			EXTERNAL DIMEN. in Inches			Depth in Inches		Colors							Units Master.	PanelFra.	Extras	CASE
						Length	Width	Height	Length	Width	Height	Lid	Case	Black	Silver	Orange	Yellow	Red	Blue	Clear*				

*Clear Micro Cases with liners and latches in: black, blue, yellow and red
 ** With wheels

	Materials	Test Specifications
Case	Copolymer Polypropylene Structural Resin	MIL STANDARD MIL-C-4150-J
Latches	ABS	
O-Ring	Neoprene Sponge	Air Transportation Association Spec. 300
Pins	Stainless Steel	
Foam	1.7 lb Polyurethane	IP 67, IP 57 in accordance EN60529/91 & IEC60529/89
Purge Valve	ABS - Stainless Steel - Neoprene	